

UPM CCK™

UPM CCK™ is a versatile clay coated kraft for high-speed converting. It's suitable for reel and sheet, fanfolding, and other applications.

- High-speed converting
- Good lay-flatness
- Low silicone consumption
- Fanfolding
- Reel and sheet applications

Recommended end-uses

Label

Product information

Regions	Europe North America Asia-Pacific Latin America Middle East & India Africa
Business contact	UPM Specialty Papers
Category	Release base papers
Grade	CCK
Reel diameter (cm)	80,0 - 120,0
Reel width (cm)	50,0 - 240,0
Core (mm)	76,0 / 153,0
Note	Core 150 mm available upon request. Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

Certificates

Product Compliance	BfR Food Certificate FDA Food Certificate EN 71-3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody PEFC Chain-of-Custody
Mill Certificates	ISO 9001 ISO 14001 ISO 22000 ISO 45001 EMAS
End of life	Recyclable

Technical target values with metric units

Basis weight (ISO 536) (g/m²)	45.0	72.0	74.0	78.0	82.0
Thickness (ISO 534) (µm)	47.0	71.0	73.0	82.0	87.0

Technical target values with imperial units

Basis weight (ISO 536) (lb/3000ft²)	27.6	44.2	45.4	47.9	50.3
Thickness (ISO 534) (mils)	1.8	2.8	2.9	3.2	3.4

Please note: Technical values are informative and subject to production variations.