

UPM CCK™ Graphic Layflat

UPM CCK™ Graphic Layflat is a clay coated kraft. It offers very good lay-flatness and has a smooth backside tailored for sensitive face materials.

- Smooth backside
- Good stiffness
- Excellent lay-flatness
- Self-adhesive graphic end-uses
- Low silicone consumption

Recommended end-uses

Label | Screen Printing | Tapes and industrial applications | Wide Format

Product information

Regions	Europe North America Asia-Pacific Latin America Middle East & India Africa
Business contact	UPM Specialty Papers
Category	Release base papers
Grade	CCK
Note	Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

Certificates

Product Compliance	BfR Food Certificate FDA Food Certificate EN 71-3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody PEFC Chain-of-Custody
Mill Certificates	ISO 9001 ISO 14001 ISO 22000 ISO 45001 EMAS
End of life	Recyclable

Technical target values with metric units

Basis weight (ISO 536) (g/m ²)	135.0
Thickness (ISO 534) (µm)	127.0

Technical target values with imperial units

Basis weight (ISO 536) (lb/3000ft ²)	82.9
Thickness (ISO 534) (mils)	5.0

Please note: Technical values are informative and subject to production variations.