

UPM CCK™ Splitback

UPM CCK Splitback is a clay coated kraft designed for sheet and reel applications where backside splitting or scoring is needed. This white C1S release base paper features excellent lay-flat properties, dimensional stability, and a low silicone consumption. UPM CCK Splitback has a backside suitable for flexo printing and offers outstanding caliper consistency for high-speed converting and demanding splitting or scoring.

- High-speed converting
- Backside splitting/scoring
- Low silicone consumption
- Reel and sheet applications

Recommended end-uses

Forms | Label

Product information

Available in	South America North America Asia-Pacific Africa Europe Middle East
Business contact	UPM Specialty Papers
Category	Release base papers
Grade	CCK
Reel diameter (cm)	75,0 - 150,0
Reel width (cm)	50,0 - 250,0
Core (mm)	71,0 / 76,0 / 153,0
Note	Core 150 mm available upon request. Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

Certificates

Product Compliance	BfR Food Certificate FDA Food Certificate EN 71/3:1988 D Safety of Toys
Fibre Certificates	FSC Chain-of-Custody PEFC Chain-of-Custody
Mill Certificates	ISO 9001 ISO 14001 ISO 22000 ISO 45001 EMAS
End of life	Recyclable

Technical target values with metric units

Basis weight (ISO 536) (g/m²)	83.0	86.0
Thickness (ISO 534) (µm)	84.0	87.0

Technical target values with imperial units

Basis weight (ISO 536) (lb/3000ft²)	50.9	52.8
Thickness (ISO 534) (mils)	3.3	3.4

Please note: Technical values are informative and subject to production variations.