

UPM Finesse classic matt H

Consistently high quality, realistic printing results and vibrant images. Use UPM Finesse when you want to impress your readers. Main end-uses for UPM Finesse are magazines, prestigious catalogs and advertising materials.

Recommended end-uses

Advertising material | Books | Brochures | Direct mailing | Magazine covers | Magazines | Newspaper supplements

Product information

Regions	Asia-Pacific
Business contact	UPM Specialty Papers
Category	Heatset web offset papers I
Description	High-white, woodfree coated paper (WFC). For printed products containing large amounts of text, the matt surface of UPM Finesse matt is the ideal solution.
Grade	Woodfree coated (WFC)
Finish	Matt
Furnish	Hardwood and softwood sulphate pulp
Printing method	Heatset web offset
Format/Size	Reels
Reel diameter (cm)	100,0 - 149,0
Reel width (cm)	21,0 - 213,0
Core (mm)	76,0 / 152,0
Wrapping	Strong kraft paper Strong moisture proof polyethylene laminated kraft paper
Note	FSC® and PEFC on request but subject to availability.

Certificates

Fibre Certificates	FSC Chain-of-Custody PEFC Chain-of-Custody
Mill Certificates	ISO 14001 ISO 9001 ISO 45001

Technical target values

Basis weight (ISO 536) (g/m ²)	64.0	70.0	80.0	90.0	100.0	105.0
Bulk (ISO 534) (cm ³ /g)	0.90	0.90	0.90	0.91	0.93	0.93
Brightness D65 (ISO 2470-2) (%)	97.0	97.0	97.0	97.0	97.0	97.0
CIE Whiteness (ISO 11475)	125.0	125.0	125.0	125.0	125.0	125.0
Opacity ISO (2471) (%)	90.0	91.0	93.0	94.0	95.0	95.0
Gloss Hunter (ISO 8254-1) (%)	30.0	30.0	32.0	32.0	32.0	32.0
Smoothness PPS 10 (ISO 8791-4) (µm)	3.0	3.0	2.8	2.8	2.8	2.8

Please note: Technical values are informative and subject to production variations.