

UPM FlexPack™ Natural

UPM FlexPack™ Natural is a stiff, bulky, and easily printable natural white C1S packaging paper with no added optical brighteners (OBA).

- Natural white
- No optical brighteners
- Stiff
- Flexo

Recommended end-uses

Bags | Coating | Lamination | Pouches, sachets | Wraps

Product information

Regions	Europe North America Asia-Pacific Latin America Middle East & India Africa
Business contact	UPM Specialty Papers
Category	Packaging papers
Grade	Coated one side (C1S)
Printing method	Flexo Offset
Reel diameter (cm)	80,0 - 120,0
Reel width (cm)	50,0 - 240,0
Core (mm)	76,0 / 153,0
Note	Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

Certificates

Product Compliance	BfR Food Certificate FDA Food Certificate EN 71-3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody PEFC Chain-of-Custody
Mill Certificates	ISO 9001 ISO 14001 ISO 22000 ISO 45001 EMAS
End of life	Recyclable

Technical target values with metric units

Basis weight (ISO 536) (g/m²)	83.0	87.0
Thickness (ISO 534) (µm)	78.0	82.0
Brightness C/2° (ISO 2470) (%)	82	82
Opacity ISO (2471) (%)	88	89
Smoothness PPS 10 (ISO 8791-4) (µm)	1.8	1.5

Technical target values with imperial units

Basis weight (ISO 536) (lb/3300ft²)	56.0	58.7
Thickness (ISO 534) (mils)	3.1	3.2
Brightness C/2° (ISO 2470) (%)	82	82
Opacity ISO (2471) (%)	88	89
Smoothness PPS 10 (ISO 8791-4) (µm)	1.8	1.5

Please note: Technical values are informative and subject to production variations.