UPM LabelCoat™

UPM LabelCoat™ is a multipurpose semi-gloss C1S label paper with a wide substance range designed for flexo printing and tailoring with HP Indigo printing.

- Wide basis range
- Compostable
- Semi-gloss
- UV-flexo
- HP Indigo

Recommended end-uses

Product labelling

Product information

Regions	Europe | North America | Asia-Pacific | Latin America | Middle East & India | Africa | China
Business contact	UPM Specialty Papers
Category	Face papers
Grade	Coated one side (C1S)
Printing method	Flexo | HP Indigo | Letterpress | Offset
Reel diameter (cm)	75,0 - 150,0
Reel width (cm)	50,0 - 250,0
Core (mm)	71,0 / 76,0 / 153,0
Note	Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

Certificates

Product Compliance	BfR Food Certificate | FDA Food Certificate | EN 71-3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody | PEFC Chain-of-Custody
Mill Certificates	ISO 9001 | ISO 14001 | ISO 22000 | ISO 45001 | EMAS
End of life	Recyclable | Home Compostable | Industrially Compostable

Technical target values with metric units

Basis weight (ISO 536) (g/m²)	**60.0**	**70.0**	**78.0**	**80.0**	**88.0**	**90.0**
Thickness (ISO 534) (µm)	52.0	60.0	67.0	68.0	76.0	78.0
Gloss Hunter (ISO 8254-1) (%)	68.0	68.0	68.0	68.0	68.0	68.0

Technical target values with imperial units

Basis weight (ISO 536) (lb/3000ft²)	**36.8**	**43.0**	**47.9**	**49.1**	**54.0**	**55.2**
Thickness (ISO 534) (mils)	2.0	2.4	2.6	2.7	3.0	3.1
Gloss Hunter (ISO 8254-1) (%)	68.0	68.0	68.0	68.0	68.0	68.0

Please note: Technical values are informative and subject to production variations.