

UPM LabelCoat™ Hotmelt

UPM LabelCoat™ Hotmelt is a semi-gloss C1S face paper designed to prevent adhesive migration and suitable for UV-flexo printing.

- For aggressive adhesives
- Semi-gloss
- UV-flexo

Recommended end-uses

Product labelling

Product information

Regions	Europe North America Asia-Pacific Latin America Middle East & India Africa China
Business contact	UPM Specialty Papers
Category	Face papers
Grade	Coated one side (C1S)
Printing method	Flexo HP Indigo Letterpress Offset
Reel diameter (cm)	80,0 - 120,0
Reel width (cm)	50,0 - 240,0
Core (mm)	76,0 / 153,0
Note	Core 150 mm available upon request. Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

Certificates

Product Compliance	BFR Food Certificate FDA Food Certificate EN 71-3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody PEFC Chain-of-Custody
Mill Certificates	ISO 9001 ISO 14001 ISO 22000 ISO 45001 EMAS
End of life	Recyclable Compostable

Technical target values with metric units

Basis weight (ISO 536) (g/m²)	80.0
Thickness (ISO 534) (µm)	67.0
Gloss Hunter (ISO 8254-1) (%)	66.0

Technical target values with imperial units

Basis weight (ISO 536) (lb/3000ft²)	49.1
Thickness (ISO 534) (mils)	2.6
Gloss Hunter (ISO 8254-1) (%)	66.0

Please note: Technical values are informative and subject to production variations.