

UPM LabelCoat™ Moistproof

UPM LabelCoat™ Moistproof is a moisture-resistant, semi-gloss C1S label paper with dimensional stability and lay-flatness, fit for UV-flexo and offset printing.

- Dimensional stability
- Moisture resistant
- Semi-gloss
- UV-flexo
- Offset

Recommended end-uses

Moisture Resistance | Product labelling

Product information

Regions	Europe North America Asia-Pacific Latin America Middle East & India Africa China
Business contact	UPM Specialty Papers
Category	Face papers
Grade	Coated one side (C1S)
Printing method	Flexo HP Indigo Letterpress Offset
Reel diameter (cm)	80,0 - 120,0
Reel width (cm)	50,0 - 240,0
Core (mm)	76,0 / 153,0
Note	Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

Certificates

Product Compliance	BfR Food Certificate FDA Food Certificate EN 71-3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody PEFC Chain-of-Custody
Mill Certificates	ISO 9001 ISO 14001 ISO 22000 ISO 45001 EMAS
End of life	Recyclable Compostable

Technical target values with metric units

Basis weight (ISO 536) (g/m ²)	70.0	75.0	80.0	90.0
Thickness (ISO 534) (µm)	62.0	64.0	68.0	78.0
Gloss Hunter (ISO 8254-1) (%)	68.0	68.0	68.0	68.0

Technical target values with imperial units

Basis weight (ISO 536) (lb/3000ft ²)	43.0	46.0	49.1	55.2
Thickness (ISO 534) (mils)	2.4	2.5	2.7	3.1
Gloss Hunter (ISO 8254-1) (%)	68.0	68.0	68.0	68.0

Please note: Technical values are informative and subject to production variations.