

UPM LabelCoat™ Thermal

Strong and stiff, UPM LabelCoat™ Thermal is a C1S label paper designed for precise thermal transfer printing, especially for logistics end-uses.

- Thermal transfer
- Logistics end-uses
- High strength
- Good stiffness

Recommended end-uses

VIP labelling

Product information

Regions	Europe North America Asia-Pacific Latin America Middle East & India Africa China
Business contact	UPM Specialty Papers
Category	Face papers
Grade	Coated one side (C1S)
Printing method	Thermal transfer
Reel diameter (cm)	80,0 - 120,0
Reel width (cm)	50,0 - 250,0
Core (mm)	76,0 / 153,0
Wrapping	Strong kraft paper Strong moisture proof polyethylene laminated kraft paper
Note	Core 150 mm available upon request. Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

Certificates

Product Compliance	BfR Food Certificate FDA Food Certificate EN 71-3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody PEFC Chain-of-Custody
Mill Certificates	ISO 9001 ISO 14001 ISO 22000 ISO 45001 EMAS
End of life	Recyclable

Technical target values with metric units

Basis weight (ISO 536) (g/m²)	62.0	65.0	70.0
Thickness (ISO 534) (µm)	61.0	64.0	68.0
Gloss Hunter (ISO 8254-1) (%)	33.0	33.0	33.0

Technical target values with imperial units

Basis weight (ISO 536) (lb/3000ft²)	38.1	39.9	43.0
Thickness (ISO 534) (mils)	2.4	2.5	2.7
Gloss Hunter (ISO 8254-1) (%)	33.0	33.0	33.0

Core 150 mm available on request.

Please note: Technical values are informative and subject to production variations.