

# UPM SCK™ Plus

Smooth, non-filler-added, transparent release base paper is tailored with your specific features. Supercalendered kraft has slightly lower transparency and density compared to glassines.

## Product information

Regions	North America
Business contact	<a href="#">UPM Specialty Papers</a>
Category	Release base papers
Grade	SCK
Converting method	Emulsion silicone coating   Solvent based silicone coating   Solventless silicone coating   UV cured silicone coating
Reel diameter (cm)	80,0 - 135,0 / 147,0
Reel width (cm)	50,0 - 220,0
Core (mm)	76,0 / 153,0
Note	Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

## Certificates

Product Compliance	FDA Food Certificate   EN 71-3: Safety of Toys   BfR Food Certificate
Fibre Certificates	FSC Chain-of-Custody   PEFC Chain-of-Custody
Mill Certificates	ISO 22000   EMAS   ISO 9001   ISO 45001   ISO 14001
End of life	Recyclable

## Technical target values with metric units

Basis weight (ISO 536) (g/m²)	94.0
Thickness (ISO 534) (µm)	81.0

## Technical target values with imperial units

Basis weight (ISO 536) (lb/3000ft²)	58.0
Thickness (ISO 534) (mils)	3.2

Please note: Technical values are informative and subject to production variations.