

# UPM Unique™ Lux Hotmelt

Preventing aggressive adhesive migration, UPM Unique™ Lux Hotmelt is a high white and glossy C1S face paper for premium labels printed with UV-flexo.

- For premium labels
- High whiteness
- Gloss
- UV-flexo

## Recommended end-uses

Premium labelling | Product labelling

## Product information

Regions	Europe   North America   Asia-Pacific   Latin America   Middle East & India   Africa
Business contact	UPM Specialty Papers
Category	Face papers
Grade	Coated one side (C1S)
Printing method	Flexo   HP Indigo   Letterpress   Offset   Rotogravure
Reel diameter (cm)	80,0 - 120,0
Reel width (cm)	50,0 - 250,0
Core (mm)	76,0 / 153,0
Wrapping	Strong kraft paper   Strong moisture proof polyethylene laminated kraft paper
Note	Core 150 mm available upon request. Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

## Certificates

Product Compliance	BfR Food Certificate   FDA Food Certificate   EN 71-3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody   PEFC Chain-of-Custody
Mill Certificates	ISO 9001   ISO 14001   ISO 22000   ISO 45001   EMAS
End of life	Recyclable

## Technical target values with metric units

Basis weight (ISO 536) (g/m²)	85.0
Thickness (ISO 534) (µm)	70.0
Gloss Hunter (ISO 8254-1) (%)	78.0

## Technical target values with imperial units

Basis weight (ISO 536) (lb/3000ft²)	52.2
Thickness (ISO 534) (mils)	2.8
Gloss Hunter (ISO 8254-1) (%)	78.0

Please note: Technical values are informative and subject to production variations.