

# UPM Brilliant™ Pro

With its eye-catching purity and superior surface properties, UPM Brilliant Pro is designed for all filmic face materials. This strong, white-shade, extra-smooth release base paper has a very low silicone demand and is suitable for roll-to-roll applications. With its high density and low thickness variation, it does an excellent job supporting filmic face laminations during die cutting.

- For filmic faces
- High density
- Superior surface properties

## Recommended end-uses

Label

## Product information

<b>Available in</b>	North America   Africa   Europe   Middle East   South America
<b>Business contact</b>	UPM Specialty Papers
<b>Category</b>	Release base papers
<b>Grade</b>	Glassine
<b>Reel diameter (cm)</b>	80,0 - 135,0
<b>Reel width (cm)</b>	50,0 - 230,0
<b>Core (mm)</b>	76,0 / 153,0
<b>Note</b>	Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

## Certificates

<b>Product Compliance</b>	BfR Food Certificate   FDA Food Certificate   EN 71/3:1988 D Safety of Toys
<b>Fibre Certificates</b>	FSC Chain-of-Custody   PEFC Chain-of-Custody
<b>Mill Certificates</b>	ISO 9001   ISO 14001   ISO 22000   ISO 45001   EMAS
<b>End of life</b>	Recyclable   Compostable

## Technical target values with metric units

<b>Basis weight (ISO 536) (g/m<sup>2</sup>)</b>	<b>60.0</b>	<b>62.0</b>	<b>64.0</b>	<b>71.0</b>	<b>72.0</b>
<b>Thickness (ISO 534) (µm)</b>	52.0	54.0	55.0	60.0	61.0

## Technical target values with imperial units

<b>Basis weight (ISO 536) (lb/3000ft<sup>2</sup>)</b>	<b>36.8</b>	<b>38.1</b>	<b>39.3</b>	<b>43.6</b>	<b>44.2</b>
<b>Thickness (ISO 534) (mils)</b>	2.0	2.1	2.2	2.4	2.4

Please note: Technical values are informative and subject to production variations.