

# UPM CCK™ Graphic

UPM CCK™ Graphic is a clay coated kraft for consistent converting and demanding self-adhesive graphic end-uses.

- Good stiffness
- Self-adhesive graphic end-uses
- Low silicone consumption
- Excellent lay-flatness

## Recommended end-uses

Label | Screen Printing | Tapes and industrial applications | Wide Format

## Product information

Regions	Europe   North America   Asia-Pacific   Latin America   Middle East & India   Africa   China
Business contact	<a href="#">UPM Specialty Papers</a>
Category	Release base papers
Grade	CCK
Reel diameter (cm)	75,0 - 150,0
Reel width (cm)	50,0 - 250,0
Core (mm)	71,0 / 76,0 / 153,0
Note	Core 150 mm available upon request. Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

## Certificates

Product Compliance	BfR Food Certificate   FDA Food Certificate   EN 71 -3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody   PEFC Chain-of-Custody
Mill Certificates	ISO 9001   ISO 14001   ISO 22000   ISO 45001   EMAS
End of life	Recyclable

## Technical target values with metric units

<b>Basis weight (ISO 536) (g/m²)</b>	<b>92.0</b>	<b>120.0</b>	<b>127.0</b>	<b>135.0</b>
Thickness (ISO 534) (µm)	81.0	116.0	123.0	130.0

## Technical target values with imperial units

<b>Basis weight (ISO 536) (lb/3000ft²)</b>	<b>56.5</b>	<b>73.7</b>	<b>78.0</b>	<b>82.9</b>
Thickness (ISO 534) (mils)	3.2	4.6	4.8	5.1

Please note: Technical values are informative and subject to production variations.