

UPM COTE G

When you have to make large, good quality print runs, but still be cost-effective, you can't go wrong with UPM Cote. It's a balanced and competitive combination of optical properties with the widest basis weight range in the market.

UPM COTE G:

Category	Rotogravure papers
Grade	Lightweight coated (LWC)
End use	Advertising material Catalogues Direct mailing Magazines
Finish	Gloss
Furnish	Chemical pulp Coating colour Mechanical pulp
Printing method	Rotogravure
Format/Size	Rolls
Reel diameter (inch)	31,0 - 59,0
Reel width (inch)	11,0 - 170,0
Core (inch)	3,0 / 6,0
Wrapping	Strong kraft paper Strong moisture proof polyethylene laminated kraft paper
Certificates and labels	EMAS EU Ecolabel FSC Chain-of-Custody ISO 14001 ISO 9001 PEFC Chain-of-Custody
Note	PEFC and FSC on request but subject to availability.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (lbs)	30.4	32.4	34.5	36.5	38.5	40.5
Brightness GE (ISO 2470-2) (%)	69.0	70.0	70.0	73.0	74.0	74.0
Opacity TAPPI (T425) (%)	86.0	87.0	88.0	88.0	89.0	89.0
Gloss Hunter (ISO 8254-1, T 480) (%)	52.0	54.0	57.0	60.0	62.0	65.0
Caliper (mils)	1.7	1.8	1.9	1.9	1.9	2.0
PPI (pages)	1176.0	1110.0	1052.0	1052.0	1052.0	1000.0

28.4# Available Upon Request and subject to availability and trim requirements.

Caliper and PPI figures are targets only.

Please note: Technical values are informative and subject to production variations.