

UPM COTE G NA

When you have to make large, good quality print runs, but still be cost-effective, you can't go wrong with UPM Cote. It's a balanced and competitive combination of optical properties with the widest basis weight range in the market.

UPM COTE G NA:

Category	Rotogravure papers
Grade	Lightweight coated (LWC)
End use	Advertising material Brochures Direct mailing Magazines
Furnish	Mechanical pulp
Printing method	Rotogravure
Format/Size	Rolls
Reel diameter (inch)	39,0 - 59,0
Reel width (inch)	15,0 - 145,2
Core (inch)	3,0 / 6,0
Wrapping	Strong kraft paper Strong moisture proof polyethylene laminated kraft paper
Certificates and labels	EMAS FSC Chain-of-Custody ISO 14001 ISO 9001 OHSAS 18001 PEFC Chain-of-Custody
Note	PEFC and FSC on request but subject to availability. EMAS at kaipola Mill.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (lbs)	30.0	32.0	34.0	36.0	38.0	40.0
Brightness GE (ISO 2470-2) (%)	71.0	71.0	71.0	71.0	71.0	71.0
Opacity TAPPI (T425) (%)	86.0	86.0	87.0	88.0	89.0	89.0
Gloss Hunter (ISO 8254-1, T 480) (%)	49.0	52.0	55.0	57.0	57.0	57.0
Caliper (mils)	1.6	1.7	1.8	1.9	2.1	2.2
PPI (pages)	1250.0	1176.0	1110.0	1052.0	952.0	910.0

28# Available Upon Request and subject to availability and trim requirements.

Caliper and PPI figures are targets only.

Please note: Technical values are informative and subject to production variations.