

UPM CREMA™ DUO

Wish to be able to tailor your label release liner to suit your needs? It's possible with these heavily calendered, transparent glassine papers. Glassines offer very good quality consistency, optimal surface properties, even thickness and strength.

UPM CREMA™ DUO:

Category	Base papers
Grade	Tapes
End use	Tapes and industrial applications
Finish	Supercalendered
Format/Size	Reels
Reel Diameter (cm)	80,0 - 138,0
Reel Width (cm)	50,0 - 230,0
Core (mm)	76,0 / 153,0
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EN 71/3:1988 D Safety of Toys FDA Food Certificate Food Approval Statement FSC Chain-of-Custody ISO 14001 ISO 22000 ISO 9001 PEFC Chain-of-Custody
Note	PEFC and FSC on request but subject to availability.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²) (lb/3000ft²)	87.0 (53.4)	120.0 (73.7)
Thickness (ISO 534) (µm) (mils)	75.0 (3.0)	103.0 (4.1)
Moisture (%)	6.5	6.5
Tensile Strength MD (kN/m) (lb/in)	9.5 (54.2)	12.0 (68.5)
Tensile Strength CD (kN/m) (lb/in)	4.5 (25.7)	6.0 (34.3)
Tear Strength MD (mN) (g)	450.0 (46.9)	680.0 (69.4)
Tear Strength CD (mN) (g)	560.0 (59.2)	850.0 (86.7)
Unger Oil Absorption TS g/m²	0.9	1.0
Unger Oil Absorption BS g/m²	1.2	1.5
Roughness PPS10 TS (µm)	1.5	1.5
Roughness PPS10 BS (µm)	2.5	2.8
L-value C/2°	66.0	66.0
a-value C/2°	5.0	5.0
b-value C/2°	20.0	20.0
Porosity BEKK (s)	250.0	250.0

Imperial values indicated in paranthesis

Please note: Technical values are informative and subject to production variations.