

UPM FINESSE GLOSS H

Technically advanced two-side coated label face papers offer superior runnability and performance. Consistent quality will allow you to run a safer and cleaner operation. The wide basis weight range offers solution for diversified applications.

UPM FINESSE GLOSS H:

Category	Face papers
Grade	C2S Woodfree coated (WFC)
End use	Product labelling
Finish	Gloss
Furnish	Hardwood and softwood sulphate pulp
Printing method	Flexo Letterpress Offset UV-flexo
Format/Size	Reels
Reel Diameter (cm)	100,0 - 125,0
Wrapping	Strong kraft paper Strong moisture proof polyethylene laminated kraft paper
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EN 71/3:1988 D Safety of Toys EU Ecolabel FSC Chain-of-Custody ISO 14001 ISO 9001 ISO 45001 PEFC Chain-of-Custody Permanent Paper ISO 9706
Note	PEFC and FSC on request but subject to availability. EES+ (Energy efficiency) certified.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²)	90.0	100.0	115.0	130.0	150.0
CIE Whiteness (ISO 11475:2017)	125.0	125.0	125.0	125.0	125.0
Gloss Hunter (ISO 8254-1) (%)	65.0	65.0	68.0	68.0	68.0
Roughness PPS10 TS (µm)	0.8	0.8	0.8	0.8	0.8
Thickness (ISO 534) (µm)	69.0	72.0	86.0	98.0	113.0

Please note: Technical values are informative and subject to production variations.