

# UPM Opalite H

Who, what, where, when? UPM Opalite has the answer. The paper is especially tailored for directories – both yellow pages and white. Very low basis weight UPM Opalite is thin, smooth and very durable with top level opacity.

## Recommended end-uses

Advertising material | Catalogues | Directories | Flyers | Inserts | Listings

## Product information

Regions	Africa   Europe   Middle East   South America
Business contact	<a href="#">UPM Communication Papers</a>
Category	Heatset web offset papers
Grade	Machine finished speciality (MFS)
Finish	Matt
Furnish	Mechanical pulp   Recycled fibre
Printing method	Heatset web offset
Format/Size	Reels
Reel diameter (cm)	100 / 125
Reel width (cm)	28 - 380
Core (mm)	76 / 150
Wrapping	Strong kraft paper   Strong moisture proof polyethylene laminated kraft paper
Note	PEFC and FSC on request but subject to availability

## Certificates

Product Compliance	EU Ecolabel
Fibre Certificates	FSC Chain-of-Custody   PEFC Chain-of-Custody
Mill Certificates	ISO 50001   EMAS   ISO 9001   ISO 45001   ISO 14001

## Technical target values

Basis weight (ISO 536) (g/m <sup>2</sup> )	34.0	36.0	38.0
Bulk (ISO 534) (cm <sup>3</sup> /g)	1.30	1.30	1.30
Brightness D65 (ISO 2470-2) (%)	60	60	60
L-value D65 (D65/10°) (ISO 5631-2)	85	85	85
a-value D65 (D65/10°) (ISO 5631-2)	0.5	0.5	0.5
b-value D65 (D65/10°) (ISO 5631-2)	4.5	4.5	4.5
Opacity ISO (2471) (%)	86	88	89
Smoothness PPS 10 (ISO 8791-4) (µm)	3.0	3.0	3.0

Please note: Technical values are informative and subject to production variations.

## Prepress guidelines

Characterisation data	FOGRA42L.txt
-----------------------	--------------