

# UPM Prego™

UPM Prego™ is a water vapour barrier paper for packaging of baked goods and food to go with a natural look and feel. It's recyclable and compostable.

- Recyclable
- Compostable
- Flexo
- Coating base

## Recommended end-uses

Bags | Coating | Wraps

## Product information

Regions	South America   North America   Asia-Pacific   Africa   Europe   Middle East
Business contact	<a href="#">UPM Specialty Papers</a>
Category	Packaging papers
Grade	Barrier papers
Printing method	Flexo   Offset
Reel diameter (cm)	90,0 - 135,0
Reel width (cm)	40,0 - 270,0
Core (mm)	76,0 / 150,0 / 153,0
Note	Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

## Certificates

Product Compliance	BfR Food Certificate   FDA Food Certificate   EN 71-3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody   PEFC Chain-of-Custody
Mill Certificates	ISO 9001   ISO 14001   ISO 22000   ISO 45001   EMAS
End of life	Recyclable   Home Compostable   Industrially Compostable

## Technical target values with metric units

<b>Basis weight (ISO 536) (g/m<sup>2</sup>)</b>	<b>45.0</b>	<b>55.0</b>
Thickness (ISO 534) (µm)	53.0	62.0
Brightness C/2° (ISO 2470) (%)	82.0	80.0
Opacity ISO (2471) (%)	72.0	75.0
WVTR 23°C / RH 50% (g/m <sup>2</sup> /d)	100	100

## Technical target values with imperial units

<b>Basis weight (ISO 536) (lb/3300ft<sup>2</sup>)</b>	<b>30.4</b>	<b>37.1</b>
Thickness (ISO 534) (mils)	2.1	2.4
Brightness C/2° (ISO 2470) (%)	82.0	80.0
Opacity ISO (2471) (%)	72.0	75.0
WVTR 23°C / RH 50% (g/m <sup>2</sup> /d)	100	100

Please note: Technical values are informative and subject to production variations.