

# UPM SCK™

Smooth, non-filler-added, transparent release base paper is tailored with your specific features. Supercalendered kraft has slightly lower transparency and density compared to glassines.

## Recommended end-uses

Label

## Product information

Regions	North America
Business contact	UPM Specialty Papers
Category	Release base papers
Grade	SCK
Converting method	Emulsion silicone coating   Solvent based silicone coating   Solventless silicone coating   UV cured silicone coating
Reel diameter (cm)	80,0 - 135,0 / 147,0
Reel width (cm)	50,0 - 220,0
Core (mm)	76,0 / 153,0
Note	Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

## Certificates

Product Compliance	FDA Food Certificate   EN 71-3: Safety of Toys   BfR Food Certificate
Fibre Certificates	FSC Chain-of-Custody   PEFC Chain-of-Custody
Mill Certificates	ISO 22000   EMAS   ISO 9001   ISO 45001   ISO 14001
End of life	Recyclable

## Technical target values with metric units

Basis weight (ISO 536) (g/m²)	60.0	65.0	66.0
Thickness (ISO 534) (µm)	54.0	59.0	60.0

## Technical target values with imperial units

Basis weight (ISO 536) (lb/3000ft²)	36.8	39.9	40.5
Thickness (ISO 534) (mils)	2.1	2.3	2.4

Please note: Technical values are informative and subject to production variations.