

# UPM SCK™

Smooth, non-filler-added, transparent release base paper is tailored with your specific features. Supercalendered kraft has slightly lower transparency and density compared to glassines.

## Recommended end-uses

Label

## Product information

<b>Regions</b>	North America
<b>Business contact</b>	<b>UPM Specialty Papers</b>
<b>Category</b>	Release base papers
<b>Grade</b>	SCK
<b>Converting method</b>	Emulsion silicone coating   Solvent based silicone coating   Solventless silicone coating   UV cured silicone coating
<b>Reel diameter (cm)</b>	80,0 - 135,0 / 147,0
<b>Reel width (cm)</b>	50,0 - 220,0
<b>Core (mm)</b>	76,0 / 153,0
<b>Note</b>	Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

## Certificates

<b>Product Compliance</b>	FDA Food Certificate   EN 71-3: Safety of Toys   BfR Food Certificate
<b>Fibre Certificates</b>	FSC Chain-of-Custody   PEFC Chain-of-Custody
<b>Mill Certificates</b>	ISO 22000   EMAS   ISO 9001   ISO 45001   ISO 14001
<b>End of life</b>	Recyclable

## Technical target values with metric units

<b>Basis weight (ISO 536) (g/m<sup>2</sup>)</b>	<b>60.0</b>	<b>65.0</b>	<b>66.0</b>
<b>Thickness (ISO 534) (µm)</b>	54.0	59.0	60.0

## Technical target values with imperial units

<b>Basis weight (ISO 536) (lb/3000ft<sup>2</sup>)</b>	<b>36.8</b>	<b>39.9</b>	<b>40.5</b>
<b>Thickness (ISO 534) (mils)</b>	2.1	2.3	2.4

Please note: Technical values are informative and subject to production variations.