

UPM Ultra matt 1.2 H

Developed especially for modern, demanding print jobs, UPM Ultra brings out even the gentlest of color tones magnificently. The versatile paper is your reliable and economical choice for magazines, catalogs, advertising material and flyers.

Recommended end-uses

Advertising material | Brochures | Direct mailing | Magazines

Product information

Regions	North America
Business contact	UPM Communication Papers
Category	Heatset web offset papers
Description	Coated groundwood paper, #4 grade.
Grade	Lightweight coated (LWC)
Finish	Matt
Furnish	Chemical pulp Coating colour Mechanical pulp
Printing method	Heatset web offset
Format/Size	Rolls
Reel diameter (inch)	35,5 - 51,0
Reel width (inch)	16,0 - 97,0
Core (inch)	3,0
Wrapping	Strong kraft paper Strong moisture proof polyethylene laminated kraft paper
Note	PEFC and FSC® on request but subject to availability.

Certificates

Fibre Certificates	FSC Chain-of-Custody PEFC Chain-of-Custody
Mill Certificates	EMAS ISO 14001 ISO 9001 ISO 45001

Technical target values

Basis weight-text (ISO 536) (lbs)	36.5	38.5	40.5	43.9	47.3
Brightness GE (ISO 2470-2) (%)	79	81	81	81	81
Opacity TAPPI (T425) (%)	88	90	91	92	92
Gloss Hunter (ISO 8254-1, T 480) (%)	20	20	20	20	20
Caliper (mils)	2.5	2.6	2.8	3.0	3.3
PPI (pages)	800	769	714	667	606

Ultra silk H new material code: 103291

UPM grades (except Blandin) are manufactured to D65 standards. Tappi measurements are estimated values. Blandin manufactured to Tappi specifications.
UPM grades are not manufactured to caliper targets, except as noted. Contact your sales team for more details, or to discuss caliper sensitive applications.

Please note: Technical values are informative and subject to production variations.