

UPM UNIQUE™ MIRROR

When overall business efficiency is what you are after, one side coated label papers offer reliable, consistent performance in various converting applications. The papers have a bright, clear and smooth printing surface.

UPM UNIQUE™ MIRROR:

Category	Label papers
Grade	One side coated (C1S)
End use	Product labelling VIP labelling
Finish	Supercalendered
Furnish	Hardwood and softwood sulphate pulp
Format/Size	Reels
Reel Diameter (cm)	70,0 - 150,0
Reel Width (cm)	40,0 - 300,0
Core (mm)	71,0 / 76,0 / 150,0 / 153,0
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EN 71/3:1988 D Safety of Toys FDA Food Certificate Food Approval Statement FSC Chain-of-Custody ISO 14001 ISO 9001 OHSAS 18001 PEFC Chain-of-Custody

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²)	80.0	90.0
CIE Whiteness (ISO 11475:2017) (%)	130.0	130.0
Gloss Hunter (ISO 8254-1) (%)	88.0	88.0
Smoothness PPS 10 (ISO 8791-4) (µm)	0.6	0.6
Moisture	4.5	4.8
Opacity (%)	87.0	89.0
Thickness (ISO 534) (µm)	64.0	73.0
Tensile Strength MD (kN/m)	5.0	5.5
Tensile Strength CD (kN/m)	2.5	2.8
Tear Strength MD (mN)	420.0	500.0
Tear Strength CD (mN)	480.0	550.0

Please note: Technical values are informative and subject to production variations.