

# UPM UniquePack™ Strong

UPM UniquePack™ Strong is a premium C1S packaging paper that combines strength and beauty. It's excellent for flexo printing with stunning results.

- High strength
- Compostable
- Flexo
- Superb visual appearance

## Recommended end-uses

Bags | Coating | Lamination | Pouches, sachets | Sacks | Wraps

## Product information

Regions	Europe   North America   Asia-Pacific   Latin America   Middle East & India   Africa
Business contact	<a href="#">UPM Specialty Papers</a>
Category	Packaging papers
Grade	Coated one side (C1S)
Printing method	Flexo   Offset
Reel diameter (cm)	90,0 - 135,0
Reel width (cm)	40,0 - 270,0
Core (mm)	76,0 / 150,0 / 153,0
Note	Note FSC™ and PEFC on request but subject to availability (FSC C014719, PEFC/02-31-80).

## Certificates

Product Compliance	BfR Food Certificate   FDA Food Certificate   EN 71-3: Safety of Toys
Fibre Certificates	FSC Chain-of-Custody   PEFC Chain-of-Custody
Mill Certificates	ISO 9001   ISO 14001   ISO 22000   ISO 45001   EMAS
End of life	Recyclable   Home Compostable   Industrially Compostable

## Technical target values with metric units

Basis weight (ISO 536) (g/m²)	70.0	80.0	90.0	100.0	110.0	120.0	130.0
Thickness (ISO 534) (µm)	65.0	74.0	83.0	95.0	102.0	110.0	120.0
Smoothness PPS 10 (ISO 8791-4) (µm)	1.2	1.2	1.2	1.2	1.2	1.2	1.2
CIE Whiteness (ISO 11475)	120.0	120.0	120.0	120.0	120.0	120.0	120.0
Opacity ISO (2471) (%)	86	87	89	92	93	94	96

## Technical target values with imperial units

Basis weight (ISO 536) (lb/3300ft²)	47.3	54.0	60.8	67.5	74.3	81.0	87.8
Thickness (ISO 534) (mils)	2.6	2.9	3.3	3.7	4.0	4.3	4.7
Smoothness PPS 10 (ISO 8791-4) (µm)	1.2	1.2	1.2	1.2	1.2	1.2	1.2
CIE Whiteness (ISO 11475)	120.0	120.0	120.0	120.0	120.0	120.0	120.0
Opacity ISO (2471) (%)	86	87	89	92	93	94	96

Please note: Technical values are informative and subject to production variations.