

UPM FINESSE GLOSS G

Consistently high quality, realistic printing results and vibrant images. Use UPM Finesse when you want to impress your readers. Main end-uses for UPM Finesse are magazines, prestigious catalogs and advertising materials.

UPM FINESSE GLOSS G:

Category	Rotogravure papers
Grade	Woodfree coated (WFC)
End use	Advertising material Brochures Catalogues Direct mailing High-quality magazines Magazine covers Magazines
Finish	Gloss
Printing method	Rotogravure
Format/Size	Reels
Reel Diameter (cm)	125,0
Reel Width (cm)	24,0 - 250,0
Core (mm)	76,0 / 152,0
Wrapping	Strong moisture proof polyethylene laminated kraft paper
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EN 71/3:1988 D Safety of Toys EU Ecolabel FSC Chain-of-Custody ISO 14001 ISO 50001 ISO 9001 OHSAS 18001 PEFC Chain-of-Custody Permanent Paper ISO 9706
Note	FSC® and PEFC™ on request but subject to availability. Reel widths 250.1-272.0 available on request.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²)	115.0	130.0
Bulk (ISO 534) (cm³/g)	0.74	0.74
Brightness D65 (ISO 2470-2) (%)	98.0	98.0
CIE Whiteness (%)	122.0	122.0
L-value D65 (D65/10°) (ISO 5631-2)	95.0	95.0
a-value D65 (D65/10°) (ISO 5631-2)	1.8	1.8
b-value D65 (D65/10°) (ISO 5631-2)	-7.6	-7.6
Opacity ISO (2471) (%)	93.0	94.5
Gloss Hunter (ISO 8254-1) (%)	80.0	80.0
Smoothness PPS 10 (ISO 8791-4) (μm)	0.7	0.7

Please note: Technical values are informative and subject to production variations.