

UPM IMPRESSE PLUS G

Unique combination of high print quality, smooth and soft surface and bulk for sheet rigidity. UPM Impresse is a high-quality supercalendered paper for advertising and magazine end-uses.

UPM IMPRESSE PLUS G:

Category	Rotogravure papers
Grade	Supercalendered (SC)
End use	Advertising material Brochures Catalogues Flyers Inserts Magazines Newspaper supplements
Finish	Silk
Furnish	Chemical pulp Fillers Mechanical pulp
Printing method	Rotogravure
Format/Size	Reels
Reel Diameter (cm)	100.0 - 125.0
Reel Width (cm)	40.0 - 432.0
Core (mm)	76.0 / 150.0
Certificates and labels	EMAS EU Ecolabel FSC Chain-of-Custody ISO 14001 ISO 9001 PEFC Chain-of-Custody
Note	PEFC™ and FSC® on request but subject to availability.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²)	48.0	51.0	54.0	57.0
Bulk (ISO 534) (cm³/g)	1.15	1.15	1.15	1.15
Brightness D65 (ISO 2470-2) (%)	80.0	80.0	80.0	80.0
L-value D65 (D65/10°) (ISO 5631-2)	90.5	90.5	90.5	90.5
a-value D65 (D65/10°) (ISO 5631-2)	-0.4	-0.4	-0.4	-0.4
b-value D65 (D65/10°) (ISO 5631-2)	-0.4	-0.4	-0.4	-0.4
Opacity ISO (2471) (%)	92.0	93.0	93.0	94.0
Gloss Hunter (ISO 8254-1) (%)	25.0	25.0	25.0	25.0
Smoothness PPS 10 (ISO 8791-4) (µm)	1.9	1.9	1.9	1.9

Please note: Technical values are informative and subject to production variations.

PREPRESS GUIDELINES:

Max. Total Area (TAC%)	375
ICC Paper profile	PSRGravure_MF.icc