

UPM JETLABEL

Are high whiteness, good printability and runnability your priorities? Then choose from these machine or supercalendered, woodfree uncoated papers for your converting purposes.

UPM JETLABEL:

Category	Label papers
Grade	Woodfree uncoated (WFU)
End use	VIP labelling
Finish	Machine finished
Furnish	Hardwood and softwood sulphate pulp
Printing method	Colour inkjet printing Colour laser printing (dry toner) Flexo Letterpress Offset
Format/Size	Reels
Reel Diameter (cm)	100,0 - 140,0
Reel Width (cm)	50,0 - 283,0
Core (mm)	71,0 / 76,0 / 152,0
Wrapping	Strong kraft paper Strong moisture proof polyethylene laminated kraft paper
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EU Ecolabel FSC Chain-of-Custody ISO 14001 ISO 9001 OHSAS 18001 PEFC Chain-of-Custody Permanent Paper ISO 9706
Note	PEFC and FSC on request but subject to availability.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²)	65.0	70.0
CIE Whiteness (%)	165.0	165.0
Opacity ISO (2471) (%)	90.0	92.0
Roughness Bendtsen (ISO 8791-2) (ml/min)	150.0	150.0
Thickness (ISO 534) (μm)	84.0	89.0
Tensile Strength MD (kN/m)	5.3	5.5
Tensile Strength CD (kN/m)	2.2	2.3
Tear Strength CD (mN)	500.0	530.0

Please note: Technical values are informative and subject to production variations.