

## UPM LABELCOAT™ FLEXOJET

When overall business efficiency is what you are after, one side coated label papers offer reliable, consistent performance in various converting applications. The papers have a bright, clear and smooth printing surface.

### UPM LABELCOAT™ FLEXOJET:

<b>Category</b>	Label papers
<b>Grade</b>	One side coated (C1S)
<b>End use</b>	Product labelling   VIP labelling
<b>Finish</b>	Softcalendered
<b>Furnish</b>	Hardwood and softwood sulphate pulp
<b>Printing method</b>	Flexo   Letterpress   Offset   Silk screen   Thermal transfer   UV-flexo   UV-inkjet
<b>Format/Size</b>	Reels
<b>Certificates and labels</b>	94/62 EC Heavy Metal Certificate   BfR Food Certificate   EMAS   EN 71/3:1988 D Safety of Toys   FDA Food Certificate   Food Approval Statement   FSC Chain-of-Custody   ISO 14001   ISO 22000   ISO 9001

## TECHNICAL TARGET VALUES:

<b>Basis Weight (ISO 536) (g/m<sup>2</sup>)</b>	78.0
<b>CIE Whiteness (%)</b>	120.0
<b>Opacity ISO (2471) (%)</b>	87.0
<b>Gloss Hunter (ISO 8254-1) (%)</b>	68.0
<b>Smoothness PPS 10 (ISO 8791-4) (μm)</b>	1.0
<b>Brightness C/2° (ISO 2470) (%)</b>	90.0
<b>Thickness (ISO 534) (μm)</b>	67.0
<b>Tensile Strength MD (kN/m)</b>	5.0
<b>Tensile Strength CD (kN/m)</b>	2.5
<b>Tear Strength MD (mN)</b>	420.0
<b>Tear Strength CD (mN)</b>	470.0

Please note: Technical values are informative and subject to production variations.