

UPM LABELCOAT™ JET

When overall business efficiency is what you are after, one side coated label papers offer reliable, consistent performance in various converting applications. The papers have a bright, clear and smooth printing surface.

UPM LABELCOAT™ JET:

Category	Label papers
Grade	One side coated (C1S)
End use	Product labelling VIP labelling
Finish	Softcalendered
Furnish	Hardwood and softwood sulphate pulp
Printing method	Flexo Letterpress Offset Silk screen Thermal transfer UV-flexo UV-inkjet
Format/Size	Reels
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EN 71/3:1988 D Safety of Toys FDA Food Certificate Food Approval Statement FSC Chain-of-Custody ISO 14001 ISO 22000 ISO 9001

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²)	78.0
CIE Whiteness (%)	80.0
Opacity ISO (2471) (%)	88.0
Gloss Hunter (ISO 8254-1) (%)	35.0
Smoothness PPS 10 (ISO 8791-4) (μm)	2.5
Moisture	4.8
Brightness C/2° (ISO 2470) (%)	80.0
Thickness (ISO 534) (μm)	82.0
Tensile Strength MD (kN/m)	6.4
Tensile Strength CD (kN/m)	3.0
Tear Strength MD (mN)	550.0
Tear Strength CD (mN)	650.0

Please note: Technical values are informative and subject to production variations.