

UPM LABELCOAT™ PRIME

When overall business efficiency is what you are after, one side coated label papers offer reliable, consistent performance in various converting applications. The papers have a bright, clear and smooth printing surface.

UPM LABELCOAT™ PRIME:

Category	Label papers
Grade	One side coated (C1S)
End use	Product labelling VIP labelling
Finish	Softcalendered
Printing method	Flexo Letterpress Offset Silk screen Thermal transfer UV-flexo UV-inkjet
Format/Size	Reels
Reel Diameter (cm)	75,0 - 150,0
Reel Width (cm)	50,0 - 250,0
Core (mm)	71,0 / 76,0 / 153,0
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EN 71/3:1988 D Safety of Toys FDA Food Certificate Food Approval Statement FSC Chain-of-Custody ISO 14001 ISO 22000 ISO 9001 PEFC Chain-of-Custody
Note	Core 150 mm available upon request. PEFC and FSC on request but subject to availability.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²)	70.0	78.0	80.0
Thickness (ISO 534) (μm)	62.0	68.0	70.0
Brightness D65 (ISO 2470-2) (%)	90.0	90.0	90.0
CIE Whiteness (%)	120.0	120.0	120.0
Opacity ISO (2471) (%)	85.0	86.0	87.0
Gloss Hunter (ISO 8254-1) (%)	66.0	66.0	66.0
Roughness PPS10 TS (μm)	1.0	1.0	1.0
Tensile Strength MD (kN/m)	4.8	5.0	5.1
Tensile Strength CD (kN/m)	2.3	2.5	2.6

Please note: Technical values are informative and subject to production variations.