

UPM PREPERSONAL, REELS

Be efficient and produce your exclusive preprinted business documents using woodfree uncoated UPM Preprint papers. Suitable for forms, invoices, statements, letterheads and direct mailing.

UPM PREPERSONAL, REELS:

| Category | Postal papers | | | |
|-------------------------|---|--|--|--|
| Grade | Woodfree uncoated (WFU) | | | |
| End use | Bespoke forms Business forms Correspondence Customized direct mail Direct mailing Transactional / transpromotional documents | | | |
| Furnish | Hardwood and softwood sulphate pulp | | | |
| Printing method | B/W inkjet printing B/W laser printing (dry toner) Colour laser printing (dry toner) Offset pre-printing | | | |
| Format/Size | Reels | | | |
| Reel Diameter (cm) | 100,0 - 125,0 | | | |
| Reel Width (cm) | 17,5 - 250,0 | | | |
| Core (mm) | 71,0 / 76,0 / 152,0 | | | |
| Wrapping | Strong kraft paper Strong moisture proof polyethylene laminated kraft paper | | | |
| Certificates and labels | 94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EU Ecolabel FSC Chain-of-Custody ISO 14001 ISO 9001 OHSAS 18001 PEFC Chain-of-Custody Permanent Paper ISO 9706 | | | |
| Note | FSC® and PEFC™ on request but subject to availability. | | | |

TECHNICAL TARGET VALUES:

| Basis Weight (ISO 536) (g/m²) | 75.0 | 80.0 | 90.0 | 100.0 |
|--|-------|-------|-------|-------|
| Bulk (ISO 534) (cm³/g) | 1.36 | 1.33 | 1.32 | 1.31 |
| CIE Whiteness (%) | 164.0 | 164.0 | 164.0 | 164.0 |
| Opacity ISO (2471) (%) | 93.0 | 93.0 | 94.0 | 95.0 |
| Roughness Bendtsen (ISO 8791-2) (ml/min) | 220.0 | 220.0 | 220.0 | 220.0 |

Please note: Technical values are informative and subject to production variations.