

UPM SCK™

Smooth, non-filler-added, transparent release base paper is tailored with your specific features. Supercalendered kraft has slightly lower transparency and density compared to glassines.

UPM SCK™:

Category	Label papers
Grade	Supercalendered kraft
End use	Product labelling VIP labelling
Finish	Supercalendered
Format/Size	Reels
Reel Diameter (cm)	80,0 - 135,0 / 147,0
Reel Width (cm)	50,0 - 230,0
Core (mm)	76,0 / 153,0
Wrapping	Strong kraft paper Strong moisture proof polyethylene laminated kraft paper
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EN 71/3:1988 D Safety of Toys FDA Food Certificate Food Approval Statement FSC Chain-of-Custody ISO 14001 ISO 22000 ISO 9001 PEFC Chain-of-Custody
Note	PEFC and FSC on request but subject to availability.

TECHNICAL TARGET VALUES:

Name	Tervasaari
Basis Weight (ISO 536) (g/m ²)	66.0
Thickness (ISO 534) (µm)	60.0
Thickness (ISO 534) mils	2.4
Opacity ISO (2471) (%)	62.0
Transparency (%)	43.0
Moisture	6.5
Unger Oil Absorption (g/m ²)	1.0
Roughness PPS10 TS (µm)	1.7
Tensile Strength MD (kN/m)	6.8
Tensile Strength CD (kN/m)	2.8
Tear Strength MD (mN)	320.0
Tear Strength CD (mN)	400.0
L-value C/2°	95.0
a-value C/2°	-1.0
b-value C/2°	8.0

Please note: Technical values are informative and subject to production variations.