

UPM SCK™ PLUS

Smooth, non-filler-added, transparent release base paper is tailored with your specific features. Supercalendered kraft has slightly lower transparency and density compared to glassines.

UPM SCK™ PLUS:

Category	Label papers
Grade	Supercalendered kraft
End use	Tapes and industrial applications Two sided silicone coating VIP labelling Product labelling
Finish	Supercalendered
Format/Size	Reels
Reel Diameter (cm)	80,0 - 135,0 / 147,0
Reel Width (cm)	50,0 - 230,0
Core (mm)	76,0 / 153,0
Wrapping	Strong kraft paper Strong moisture proof polyethylene laminated kraft paper
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EN 71/3:1988 D Safety of Toys FDA Food Certificate Food Approval Statement FSC Chain-of-Custody ISO 14001 ISO 22000 ISO 9001 PEFC Chain-of-Custody
Note	PEFC and FSC on request but subject to availability.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²)	94.0
Thickness (ISO 534) (μm)	81.0
Thickness (ISO 534) mils	3.2
Transparency (%)	35.0
Moisture	6.5
Unger Oil Absorption (g/m²)	0.8
Roughness PPS10 TS (μm)	1.7
Tensile Strength MD (kN/m)	9.5
Tensile Strength CD (kN/m)	4.0
Tear Strength MD (mN)	540.0
Tear Strength CD (mN)	700.0
L-value C/2°	94.0
a-value C/2°	-1.0
b-value C/2°	7.0

Please note: Technical values are informative and subject to production variations.