

UPM UNIQUEPACK™

Looking for a great price-quality ratio for your packaging? One side coated papers have a bright, clear and smooth printing surface. It's your choice when you need reliable and consistent performance in various converting applications.

UPM UNIQUEPACK™:

Category	Packaging papers
Grade	One side coated (C1S)
End use	Biscuits and other food wrapping areas Chocolate wrapping Foil-stamping PP/PE coating and laminating base Soup pouches
Finish	Softcalendered Supercalendered
Furnish	Hardwood and softwood sulphate pulp
Printing method	Digital reel fed printing Flexo Letterpress Offset Rotogravure Silk screen Thermal transfer
Format/Size	Reels
Reel Diameter (cm)	70,0 - 150,0
Reel Width (cm)	50,0 - 90,0
Core (mm)	71,0 / 76,0 / 150,0 / 153,0
Wrapping	Strong moisture proof polyethylene laminated kraft paper
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EN 71/3:1988 D Safety of Toys FDA Food Certificate Food Approval Statement FSC Chain-of-Custody ISO 14001 ISO 22000 ISO 9001 PEFC Chain-of-Custody
Note	PEFC and FSC on request but subject to availability.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²)	43.0	50.0	60.0	70.0	80.0	85.0	90.0
Thickness (ISO 534) (μm)	41.0	43.0	51.0	59.0	68.0	72.0	76.0
Brightness D65 (ISO 2470-2) (%)	89.0	89.0	92.0	92.0	92.0	92.0	92.0
CIE Whiteness (%)	118.0	118.0	120.0	120.0	120.0	120.0	120.0
Gloss Hunter (ISO 8254-1) (%)	72.0	72.0	75.0	75.0	75.0	76.0	76.0
Roughness PPS10 TS (μm)	0.8	0.8	0.8	0.7	0.7	0.7	0.7

Please note: Technical values are informative and subject to production variations.